

# ANTISTATICA

## FEATURES

- Used for transfer of fuels and other flammable liquids.
- Made from a blend of nitrile rubber and PVC, with conductive properties and added UV barrier to prevent damage from UV radiation.
- This method of achieving conductivity removes the risk of breaking conductive wires commonly used in rubber hoses for this purpose

## DESIGN

- The rubber blend is extruded through a circular woven reinforcement made from filament polyester yarn.
- This production method gives a very strong bonding between cover and lining as well as firmly encapsulating the reinforcing polyester.
- The hose has high resistance against commonly used chemicals.

## ADVANTAGES

- Due to the interlocking circular weave, the hose does not stretch when pulled. For the same reason, it has a very high pressure rating o wall thickness ratio.
- Light weight.
- Highly flexible.



## TECHNICAL DATA

| INNER DIAMETER |             | WALL THICKNESS |     | WEIGHT   |        | BURST PRESSURE |     | TENSILE STRENGTH |      |
|----------------|-------------|----------------|-----|----------|--------|----------------|-----|------------------|------|
| Inch           | mm          | Inch           | mm  | Lbs / ft | Kg / m | Psi            | Bar | x1000 kbs        | Tons |
| 3/4            | 20,0 + 1,6  | 0,09           | 2,3 | 0,14     | 0,21   | 1450           | 100 | 4,2              | 1,9  |
| 1              | 25,5 + 1,6  | 0,10           | 2,5 | 0,19     | 0,28   | 1450           | 100 | 5,1              | 2,3  |
| 1 1/2          | 38,0 + 1,6  | 0,09           | 2,2 | 0,21     | 0,32   | 870            | 60  | 6,4              | 2,9  |
| 2              | 51,0 + 2,0  | 0,09           | 2,2 | 0,27     | 0,41   | 655            | 45  | 8,4              | 3,8  |
| 2 1/2          | 65,0 + 2,0  | 0,09           | 2,2 | 0,36     | 0,54   | 655            | 45  | 9,3              | 4,2  |
| 3              | 76,0 + 2,0  | 0,12           | 3,1 | 0,65     | 0,97   | 725            | 50  | 17,9             | 8,1  |
| 4              | 102,0 + 2,5 | 0,13           | 3,3 | 0,90     | 1,35   | 580            | 40  | 22,5             | 10,2 |
| 5              | 127,0 + 3,0 | 0,13           | 3,3 | 1,13     | 1,70   | 435            | 30  | 26,9             | 12,2 |
| 6              | 154,0 + 3,0 | 0,15           | 3,8 | 1,51     | 2,25   | 610            | 42  | 36,6             | 16,6 |

